

IP65 STARRY SKY LIGHT PRODUCT MANUAL



Thank you for using the RGB laser projector. For the sake of safety and better operation of this projector, please read this manual carefully before use and operation, lest incur any personal injury or damage to the projector.


Protection class: IP65
Ambient temperature: -20°C~+45°C
Projection distance: ≥50m
Service life: more than 20000h
Control system: DMX512/automatic/master-slave
Voltage power: AC 110/220V 50/60Hz
Power factor: 50W
Product net weight: 5.5KG
Product size: 26*31*27.5cm (Including handle)
Package size: 43.5*26*20cm
Packing weight: 6.5KG

Operating Instructions




Menu Up Down Confirm

1. Menu display and functions (all functions can be saved by selecting them and then pressing the confirmation key)



STARSHINE LIGHTS
PRODUCT MANUAL





STARSHINE LIGHTS PRODUCT MANUAL



Show	Function Description
Axxx	DMX Address: 001-512
T3Cx	T3Cw: Forward, T3Cc: Reverse, T3Cn: Random Forward/Reverse
P1xx	Motor Speed (P100-P130)
Auxx	Color Selection (AU01-AU07)
FFxx	Dual Laser Synchronous Jump, Values 1-9 for Speed Adjustment
E1xx	Dual Laser Synchronous Gradient, Values 1-9 for Speed Adjustment
C1xx	Dual Laser Synchronous Pulse, Values 1-9 for Speed Adjustment
CPxx	Dual Laser Asynchronous Jump, Values 1-9 for Speed Adjustment
EExx	Dual Laser Asynchronous Gradient, Values 1-9 for Speed Adjustment
CCxx	Dual Laser Asynchronous Pulse, Values 1-9 for Speed Adjustment
S1 1	Voice-Controlled Color Changing
S2 1	Voice-Controlled Strobe

2, DMX512 Channel Description

Channel	Numerical	Functional Description
CH1	0-255	Overall dimming
CH2	0-255	Red light brightness
CH3	0-255	Green light brightness
CH4	0-255	Blue light brightness
CH5	0-255	Red light 2 brightness
CH6	0-255	Green light 2 brightness
CH7	0-255	Blue light 2 brightness
CH8	0-255	Strobe speed
CH9	0-50	CH2-CH8 valid
	51-100	Color selection
	101-120	Jumping
	121-140	Gradual change
	140-160	Pulsing
	160-180	Multi-color jumping
	180-200	Multi-color gradual change
	200-220	Multi-color pulse changing
	220-255	Voice control
CH10	0-255	Jumping and gradual change speed control
CH11	0-255	Motor control



STARSHINE LIGHTS PRODUCT MANUAL

No smoke effect



Smoke effect

